



Cactus® Double Coated Film Tape

Technical Data Sheet No. N2910

Product Information

Cactus® Double Coated Film Tape N2910 is a solvent-based acrylic pressure sensitive adhesive tape which offers high initial tack and excellent shear strength for quick bonding results. Ideal for LSE substrates and other kinds of porous materials, and has high resistance to alkalization and low temperatures.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 4 mil (0.11 ± 0.01 mm)
Carrier	: 1/2 mil PET Film	Tack	: J. Dow No. 26
Liner Thickness	: 6 mil	Peel Adhesion	: PSTC-3 77.59 oz/inch (2.2kg/25mm)
Liner Material	: Bleached Kraft Paper	Shear Strength PSTC-7	: Over 24 hrs with 35.3 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Density	: #76 (110 g/m ²)	Service Temperature	: -40°F ~ 194°F (-40°C ~ 90°C)
Liner Color	: White	Tape Color	: Clear

Applications

- For heat breaking, gasketing and sealing of materials
- General purpose holding and mounting applications
- Excellent for laminating sailcloth seams and other seaming applications

Storage and Shelf Life

For best results, store this product at 72°F (22°C) and 50% relative humidity, use within 2 years from date of receipt.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.