



Cactus® Double Coated Film Tape

Technical Data Sheet No. P2970

Product Information

Cactus® Double Coated Film Tape P2970 is a solvent-based acrylic pressure sensitive adhesive which offers high initial tack for quick bonding results. Ideal for general purpose industrial applications such as bonding, fixing, mounting, and splicing. Made of enhanced PET film carrier and features convenient and clean removability when bonded to various substrates.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 3.5 mil (0.09 ± 0.005 mm)
Carrier	: 1/2 mil PET Film	Tack	: J. Dow No. 20
Liner Thickness	: 4.7 mil	Peel Adhesion	: PSTC-3 42.3 oz/in (1.2kgs/25mm)
Liner Material	: Polycoated Kraft Paper	Shear Strength PSTC-7	: Over 24 hrs with 35.2 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Density	: #74 (110 g/m ²)	Service Temperature	: -4°F ~ 144°F (-20°C ~ 80°C)
Liner Color	: White	PH Value	: 7.0
Tape Color	: Clear		

Applications

- For general purpose industrial applications such as bonding, fixing, mounting and splicing
- Mounting of nameplates, trophies and signs
- Bonding of sporting goods - tennis, shoes, leather, etc.
- Ideal for Stationery Industry

Storage and Shelf Life

For best results, store this product at 72°F (22°C) and 50% relative humidity, use within 2 years from date of receipt.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.