



Cactus® Double Coated Foam Tape

Technical Data Sheet No. R2808

Product Information

Cactus® Double Coated Foam Tape R2808 is a cost-effective solvent-based rubber pressure sensitive adhesive which offers very high tack and excellent shear strength. Ideal for long-term indoor applications and highly recommended for die cutting processes. Reinforced with White 4 PCF cross-linked polyethylene foam, good for mounting purposes and provides excellent adhesion to various substrates.

Composition & Physical Properties

Adhesive System	: Solvent Rubber	Tape Thickness	: 1/32" (0.8 ± 0.1mm)
Carrier	: Polyethylene Foam	Loop Tack	: FINAT-9 123.45 oz/inch (3.5 kg/25mm)
Foam Density	: 4 PCF	Peel Adhesion	: PSTC-3 88.18 oz/inch (over 2.5 kg/25mm)
Liner Thickness / Density	: 3.5 mil #60 (90 g/m ²)	Shear Strength PSTC-9	: Over 500 hrs with 70.6 oz loading on 1" x 1" (2.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Material	: SCK Paper	Service Temperature	: 50°F ~ 122°F (10°C ~ 50°C)
Liner Color	: White	Tape Color	: White

Applications

- Excellent for bonding heavy-duty hanger hooks under room temperature
- For joining and mounting of nameplates, point of purchases, plastics, mirrors and emblems
- For fixing plastic or metal articles, e.g. stationeries, kitchenware, bathroom accessories, etc

Storage and Shelf Life

For best results, store this product at 72 °F (22 °C) and 50% relative humidity, use within 2 years from date of receipt.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.