



Cactus® Double Coated Foam Tape

Technical Data Sheet No. R485W

Product Information

Cactus® Double Coated Foam Tape R485W is a solvent-based rubber pressure sensitive adhesive tape that offers immediate adhesion bond and excellent tack, reinforced with white 4 PCF closed cell durable polyethylene foam carrier, ideal for the window fabricators who seek to improve operator efficiency. Good resistance to vibration and impact. AAMA verified.

Composition & Physical Properties

Adhesive System : Solvent Rubber	Tape Thickness : 1/16" (1.5 ± 0.1mm)
Carrier : Polyethylene Foam	Loop Tack (FINAT-9) : 176 oz/inch (5.0 kg / 25mm) <i>Carrier broken</i>
Foam Density : 4 PCF	Peel Adhesion (PSTC-3) : 123 oz/inch (3.5 kg / 25mm) <i>Carrier broken</i>
Liner Thickness : 4 mil	Shear Strength PSTC-7 : Over 72 hrs with 35.2 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Material : Polyolefin	Service Temperature : -22°F ~ 176°F (-30°C ~ 80°C)
Liner Color : Blue	Tape Color : White

Applications

- Flexible soft foam can seal up effectively against water, dust and light.
- For joining and mounting of nameplates, point of purchases, plastics, mirrors and emblems
- For window glazing applications

Storage and Shelf Life

For best results, store this product at 72 °F (22 °C) and 50% relative humidity, use within 2 years from date of receipt.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.