



**Cactus® Double Coated Tissue Tape**

**Technical Data Sheet No. F2410**

**Product Information**

Cactus® Double Coated Tissue Tape F2410 is an acrylic solvent based adhesive that features a high tack adhesive system, providing quick bonding results, and good resistance to temperature, chemicals, and UV. This thin tissue tape fastens in tight spaces and adheres to smooth surfaces effectively.

**Composition & Physical Properties**

Adhesive System : Solvent Acrylic	Tape Thickness : 2.4 mil (0.06 ± 0.005 mm)
Carrier : Tissue	Tack : J. Dow No. 16
Liner Thickness : 5 mil	Loop Tack : FINAT-9 52.9 oz/inch (1.5 kg/25mm)
Liner Material : Bleached Kraft Paper	Peel Adhesion PSTC-3 : 45.6 oz/inch (1.3 kg/25mm)
Liner Density : #74 (110 g/m <sup>2</sup> )	Shear Strength PSTC-7 : Over 24 hrs with 2.2 lb loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Color : White	Heat Resistance : Over 24 hrs with 1.1 lb loading on 1.0kg/25mm x 25mm at 176°F (80°C)
Tape Color : White	Service Temperature : -22°F ~ 212°F (-30°C ~ 100°C)

**Applications**

- Fastening to smooth surfaces such as metal plates, film and plastic parts with high adhesion.
- Fixing and laminating of various substrates of electronic components and devices.

**Storage and Shelf Life**

For best results, store this product at 72°F (22°C) and 50% relative humidity, use within 2 years from date of receipt.

**Disclaimer and Limitation of Liability**

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.