



Cactus® Double Coated Foam Tape

Technical Data Sheet No. N2208

Product Information

Cactus® Double Coated Foam Tape N2208 is an acrylic solvent based adhesive, offers high shear and tack for secure bonding applications. Reinforced with White 6 PCF cross-linked polyethylene foam tape with easy remove liner, allows excellent conformability to irregular and contour surfaces.

Composition & Physical Properties

| | | | |
|-----------------|------------------------------|---------------------|--|
| Adhesive System | : Solvent Acrylic | Tape Thickness | : 1/32" (0.8 ± 0.1 mm) |
| Carrier | : Polyethylene Foam | Tack | : J. Dow No. 18 |
| Foam Density | : 6 PCF | Peel Adhesion | : PSTC-3 63.5 oz/in (1.8 ± 0.1 kg/25mm) |
| Liner Material | : Glassine Paper | Shear Strength | : Over 24 hrs with 35.3 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C) |
| Liner Thickness | : 3 mil | Service Temperature | : -22°F ~ 194°F (-30°C ~ 90°C) |
| Liner Density | : #60 (90 g/m ²) | Tape Color | : White |
| Liner Color | : White | | |

Applications

- Mounting and joining nameplates, signs, plaques, point of purchase, plastic hooks etc.
- Excellent for long-term mounting of mirror trim.
- Ideal for general purpose indoor and outdoor mounting and joining applications.
- For permanent bonding and repair of metal or plastic articles, e.g. houseware, kitchenware, bathroom accessories, etc.

Storage and Shelf Life

For best result, store this product at 72 °F (22 °C) and 50% relative humidity, use within 2 years from date of receipt.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.