



**V. HIMARK USA INC.**  
Leading you the way to Productivity and Profitability



## Cactus® Double Coated Foam Tape

Technical Data Sheet No. PR218

### Product Information

Cactus® Double Coated Foam Tape PR218 is a solvent-based rubber adhesive which offers high shear strength, ideal for secure bonding applications, semi-removable rubber adhesive coatd on both sides, easily peels from substrates leaving no trace of sticky residue. PR218 is reinforced with white 8 PCF cross-linked polyethylene foam, provides excellent conformability and excellent bonding for irregular surfaces and various substrates, good resistance to moisture and best for temporary mounting purposes.

### Composition & Physical Properties

Adhesive System	: Solvent Rubber	Thickness	: 1/32" (0.8 ± 0.1 mm)
Carrier	: Polyethylene Foam	Loop Tack	: FINAT-9 98.76 oz/inch (2.8kg/25mm)
Foam Density	: 8 PCF	Peel Adhesion	: PSTC-3 63.49 oz/inch (1.8kg/25mm)
Liner Material	: PE Laminated Kraft Paper	Shear Strength	: Over 100 hrs with 4.4 lbs loading on 1" x 1" (2.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Thickness	: 3 mil	Service Temperature	: 50°F ~ 122°F (10°C ~ 50°C)
Liner Color	: Light Yellow		
Tape Color	: White		

### Applications

- Specifically designed for heavy-duty loading applications that requires easy and clean removal from substrate.
- Temporary mounting and fixing of nameplates, plastic trims, signs and emblems for indoor use.

### Storage and Shelf Life

For best result, store this product at 72 °F (22 °C) and 50% relative humidity, use within 2 years from date of receipt.

### Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.



